


THU

Elevatore idraulico duplex
Duplex fork lift



Montante duplex con cuscinetti
Duplex profile with bearing



Cuscinetto assiale
Axial bearing

DATI TECNICI - TECHNICAL DETAILS

MOD. COD.	 nr.	 Kg	 A	 B	 E	 L	 Kg
THU 13-25	1	1.300	250 cm	10+10 cm	10°+10°	203 cm	435
THU 13-32	1	1.300	320 cm	10+10 cm	10°+10°	230 cm	455
THU 13-36	1	1.300	360 cm	10+10 cm	10°+10°	260 cm	480
THU 17-25	1	1.700	250 cm	10+10 cm	10°+10°	203 cm	445
THU 17-32	1	1.700	320 cm	10+10 cm	10°+10°	230 cm	465
THU 17-36	1	1.700	360 cm	10+10 cm	10°+10°	260 cm	490
THU/GV Grande Visibilità / Great visibility / Une grande visibilité / Gute sicht / Gran visibilidad							
THU/GV 13-25	2	1.300	250 cm	10+10 cm	10°+10°	203 cm	460
THU/GV 13-32	2	1.300	320 cm	10+10 cm	10°+10°	230 cm	480
THU/GV 13-36	2	1.300	360 cm	10+10 cm	10°+10°	260 cm	505
THU/GV 17-25	2	1.700	250 cm	10+10 cm	10°+10°	203 cm	470
THU/GV 17-32	2	1.700	320 cm	10+10 cm	10°+10°	230 cm	490
THU/GV 17-36	2	1.700	360 cm	10+10 cm	10°+10°	260 cm	515