

tifermec[®]

RETROESCAVATORI

BACKHOE • HECKBAGGER • PELLE RÉTRO • RETROEXCAVADORA



Il futuro è il nostro lavoro




[a richiesta • attachments • auf Anfrage • accessoires • accesorios]



- **Benna letame**
- Manure bucket
- Mistschaufel
- Pince à fumier
- Cuchara estiércol



- **Benna scavo**
- Digging bucket
- Baggerschaufel
- Godet d'excavation
- Cuchara excavación



- Benna scavo fossi
- Ditching bucket
- Grabenräumer
- Godet excavation fossés
- Cuchara excavación fosos



- **Benna pulizia fossi**
- Trench clearing bucket
- Reinigungsschaufel
- Godet nettoyage fossés
- Cuchara limpieza fosos



- **Testata trinciante**
- Chopping head
- Mulchkopf
- Tête broyeurse
- Cabezal triturador



- **Trivella idraulica**
- Hydraulic post hole digger
- Erdbohrer
- Tariere hydraulique
- Barrenadora hidráulica



- **Martello demolitore idraulico**
- Jackhammer
- Schlaghammer
- Marteau piqueur hydraulique
- Martillo hidráulico



- **Pinza carica tronchi**
- Lob grab
- Holzgreifer
- Pince pour tronc
- Alicates para el manejo

serie
Dig
Dig

RETROESCAVATORI

BACKHOE • HECKBAGGER • PELLE RÉTRO • RETROEXCAVADORA



- **DOPPIO MARTINETTO DI ROTAZIONE 180° CON FRENO**
- DUAL CYLINDER FOR 180° SWIVEL AND END-OF-STROKE BRAKE
- 180° VERSCHWENKUNG ÜBER DOPPELZYLINDER UND BREMSE AM HUBENDE
- DOUBLE VÉRIN DE ROTATION 180° ET FREIN DE FIN COURSE
- DOBLE MARTINETE DE ROTACIÓN 180° CON FRENO DE FINAL RECORRIDO



Dig Dig

- **VALVOLE DI BLOCCO SUGLI STABILIZZATORI**
- LOCKING VALVES AT STABILIZERS
- HYDRAULISCHE STÜTZFÜßE EINZELN ANGESTEUERT
- SOUPAPES DE BLOCAGE SUR LES PIEDS DE STABILISATION
- VÁLVULAS DE BLOQUEO EN LOS ESTABILIZADORES

Dig Dig



- **POMPA IN GHISA AD ALTO RENDIMENTO**
- HIGH EFFICIENCY CAST IRON PUMP
- PUMPE AUS GUSSEISEN MIT HOHER LEISTUNG
- POMPE EN FONTE DE HAUT RENDEMENT
- BOMBA EN HIERRO FUNDIDO DE ALTO RENDIMIENTO

MOD. TX

- **MULTIPOSIZIONE DI LAVORO**
- WORKING MULTIPOSITIONING
- MULTI-ARBEITSPOSITION
- MULTIPOSITION DE TRAVAIL
- MULTIPOSICIÓN DE TRABAJO

DATI TECNICI / SPECIFICATIONS TECHNISCHE DATEN / CARACTÉRISTIQUES / DATOS TÉCNICOS

MOVIMENTAZIONE BRACCI / ARM MOTION BEWEGUNG ARME / MOUVEMENT DES BRAS / MOVIMIENTO BRAZOS			50 TX	55 TX	60 TX	65 TX			
A	(mm.)	A	(mm.)	2100	2200	2500	2600		
B	(mm.)	B	(mm.)	1900	1900	2300	2300		
C	(mm.)	C	(mm.)	2800	2800	3200	3200		
D	Raggio d'azione Working radius - Aktionsradius	(mm.)	D	Rayon d'action Rayo de acción	(mm.)	2900	2950	3270	3320
Larghezza telaio trasabile Traveling frame width - Breite Verschiebungsgestell		(mm.)	Largeur du châssis avec translation Ancho bastidor trasladable		(mm.)	1400	1600	1600	1800
Forza di strappo al dente Bucket breakout force - Reißkraft am Zahn		(kg.)	Force d'arrachement Fuerza de tiro al diente		(kg.)	2300	2300	2600	2600
Angolo di rotazione Rotation angle - Rotationswinkel			Angle de rotation Angulo de rotación		180°				
Portata max pompa Pump max delivery - Max. Fähigkeit der Pumpe		(lt/min)	Débit max pompe Capacidad máx. de la bomba		(lt/min)	21	21	24	24
Pressione di taratura Working pressure - Arbeitsdruck		(Bar)	Pression de travail Presión de taraje		(Bar)	180			
Capacità serbatoio Tank capacity - Fassungsvermögen des Tanks		(lt.)	Capacité du réservoir Capacidad depósito		(lt.)	35			
Benna scavo Digging bucket - Grabschaufel		(mm.)	Benne d'excavation Cuchara excavación		(mm.)	250÷600			
Peso con benna Weight with bucket - Gewicht mit Schaufel		(Kg.)	Poids avec godet Peso con cuchara		(Kg.)	550	570	640	670
Massa minima trattore Min. tractor's weight - Mindestgewicht Zugmaschine		(kg.)	Poids min. tracteur Masa mínima tractor		(kg.)	1900	1900	2200	2300
Potenza minima trattore Min. power requirements - Zugmaschine		(HP)	Puissance min. requise Potencia mínima tractor		(HP)	30	30	40	40



serie
Dig
Dig

RETROESCAVATORI

BACKHOE • HECKBAGGER • PELLE RÉTRO • RETROEXCAVADORA



- È OBBLIGATORIO L'USO DEL KIT BLOCCAGGIO
- USE OF THE LOCKING DEVICE IS COMPULSORY
- DIE VERWENDUNG DES SPERR-KITS IST ZWINGEND VORGESCHRIEBEN
- L'UTILISATION DU KIT DE BLOCAGE EST OBLIGATOIRE.
- USO OBLIGATORIO DEL KIT BLOQUEO



DATI TECNICI / SPECIFICATIONS TECHNISCHE DATEN / CARACTÉRISTIQUES / DATOS TÉCNICOS

MOVIMENTAZIONE BRACCI / ARM MOTION BEWEGUNG ARME / MOUVEMENT DES BRAS / MOVIMIENTO BRAZOS			70 TX	75 TX	80 TX	85 TX	90 TX	100 TX			
A	(mm.)	A	(mm.)	2700	2800	3000	3100	3500	4200		
B	(mm.)	B	(mm.)	2500	2500	2700	2700	3100	3850		
C	(mm.)	C	(mm.)	3500	3500	3700	3700	4200	4950		
D	Raggio d'azione Working radius - Aktionsradius	(mm.)	D	Rayon d'action Rayo de acción	(mm.)	3500	3550	3800	3850	4000	5100
Larghezza telaio traslabile Traveling frame width - Breite Verschiebungsgestell		(mm.)	Largueur du châssis avec translation Ancho bastidor trasladable		(mm.)	1800	2000	1800	2000	2000	2000
Forza di strappo al dente Bucket breakout force - Reißkraft am Zahn		(kg.)	Force d'arrachement Fuerza de tiro al diente		(kg.)	2800	2800	2900	2900	3550	5600
Angolo di rotazione Rotation angle - Rotationswinkel			Angle de rotation Angulo de rotación			180°		180°			
Portata max pompa Pump max delivery - Max. Fähigkeit der Pumpe		(lt/min)	Débit max pompe Capacidad máx. de la bomba		(lt/min)	30	30	38	38	57	78
Pressione di taratura Working pressure - Arbeitsdruck		(Bar)	Pression de travail Presión de taraje		(Bar)	180			180		
Capacità serbatoio Tank capacity - Fassungsvermögen des Tanks		(lt.)	Capacité du réservoir Capacidad depósito		(lt.)	50	50	50	50	70	70
Benna scavo Digging bucket - Grabschaufel		(mm.)	Benne d'excavation Cuchara excavación		(mm.)	250÷400	250÷400	250÷400	250÷400	250÷800	250÷800
Peso con benna Weight with bucket - Gewicht mit Schaufel		(Kg.)	Poids avec godet Peso con cuchara		(Kg.)	770	800	860	890	1200	1700
Massa minima trattore Min. tractor's weight - Mindestgewicht Zugmaschine		(kg.)	Poids min. tracteur Masa mínima tractor		(kg.)	2500	2600	2800	2900	4000	6000
Potenza minima trattore Min. power requirements - Zugmaschine		(HP)	Puissance min. requise Potencia mínima tractor		(HP)	60	60	70	70	100	120

- PIEDI STABILIZZATORI INDIPENDENTI
- INDEPENDENT STABILIZERS
- UNABHÄNGIGE STABILISIERUNGSFÜßE
- PIEDS DE STABILISATION INDÉPENDANTS
- PIES ESTABILIZADORES INDEPENDIENTES

