

RIBALTAMENTO IDRAULICO POSTERIORE	DIMENSIONE CASSONE	PORTATA OMOLOGATA	RUOTE
B125P	2.30x1.50x0.40	15 Q.LI	205.15 D
B125GCF	2.50x1.50x0.40	15 Q.LI	205.15 D
RIBALTAMENTO IDRAULICO TRILATERALE	DIMENSIONE CASSONE	PORTATA OMOLOGATA	RUOTE
B125P	2.30x1.50x0.40	15 Q.LI	205.15 D
B125GCF	2.50x1.50x0.40	15 Q.LI	205.15 D
B220	2.50x1.60x0.40	25 Q.LI	10.0/80 12 10t
B225	2.70x1.70x0.40	34 Q.LI	10.0/75 15.3 10t
B228	2.90x1.80x0.40	37 Q.LI	10.0/75 15.3 12t
B40	3.20x1.90x0.40	47 Q.LI	11.5/80 15.3 12t
B552	3.00x1.80x0.50	50 Q.LI	305/70 R19.5 I
B550	3.40x2.00x0.50	50 Q.LI	11.5/80 15.3 14t
B552L	3.50x1.80x0.50	50 Q.LI	305/70 R19.5 I
B555	3.70x2.00x0.50	50 Q.LI	11.5/80 15.3 14t
B502L	4.00x2.20x0.50	50 Q.LI	13.0/65-18 16t
RIBALTAMENTO MECCANICO POSTERIORE	DIMENSIONE CASSONE	PORTATA OMOLOGATA	RUOTE
B125LCF(V)	1.90x1.30x0.30	15 Q.LI	195.14 D
B125LCF	2.00x1.40x0.30	15 Q.LI	205.15 D
B125P	2.30x1.50x0.40	15 Q.LI	205.15 D
B125GCF	2.50x1.50x0.40	15 Q.LI	205.15 D
B220	2.50x1.60x0.40	25 Q.LI	10.0/80 12 10t
B225	2.70x1.70x0.40	34 Q.LI	10.0/75 15.3 10t
B228	2.90x1.80x0.40	37 Q.LI	10.0/75 15.3 12t
B40	3.20x1.90x0.40	47 Q.LI	11.5/80 15.3 10t
B550	3.40x2.00x0.50	50 Q.LI	11.5/80 15.3 10t
TRILATERALI 60 Q.	DIMENSIONE CASSONE	PORTATA OMOLOGATA	RUOTE
B552 FJ	3.00x1.80x0.50	60 Q.LI	305/70 R19.5 I
B552L FJ	3.50x1.80x0.50	60 Q.LI	305/70 R19.5 I
B555 FJ	3.70x2.00x0.50	60 Q.LI	11.5/80 15.3 16t
B502L	4.00x2.20x0.50	60 Q.LI	13.0/65-18 16t
51 AL	4.70x2.40x0.60	60 Q.LI	435/50 R19.5 I
TRILATERALI RUOTE GEMELLATE	DIMENSIONE CASSONE	PORTATA OMOLOGATA	RUOTE
B555 G	3.70x2.00x0.50	50 Q.LI	215/75 R17.5 I gem.
B502 G	4.00x2.00x0.50	50 Q.LI	215/75 R17.5 I gem.